

# Petrotex 8080

Carboxylated Styrene-butadiene Emulsion Latex

<b>Product</b>	data:
----------------	-------

Solid Content 50±1

cР Viscosity 300±100

Brookfield SP.2.12rpm at 20 °C

pH at (25 °C) 8±1

Density q/cm<sup>3</sup> 1.03±0.005

**Surface Tension** (mN/m) at 25 °C 42±5

 $^{\circ}C$ **MFFT** 0

Milky White **Appearance** 

### **Application:**

Back coating of artificial grass (Turf)

### Advantages:

Soft and flexible film with stable foam

Great adhesion provides strong clasp of the pile

Excellent water resistance and low water absorption

Excellent filler acceptance and compound stability

# Storage:

It must be stored between 5- 40 °C. keep away from direct heat and sunlight.

Avoid freezing.

Keep containers closed when not in use.

Mix prior to use.

#### Shelf life:

One year since manufacturing.

It can be used after a year if the test result meets standard.

## **Delivery:**

It can be transported in flexi tanks, IBCs and drums.

(+9821) 42 437

(+9821) 88 62 48 72

#### WWW.PETROTEXIRAN.COM

Unit 5,No 9, Masumi St. North Sheikh Bahayi St.MollasadraSt. Tehran, IRAN

Postal Code: 1991834994









